



## MODEL 3350 / 3353 SUPERDUTY 48" SLITTER



### *The Superduty*

*The Superduty 48" Sheet Slitters offers a new dimension to multi-cutting equipment. To serve the processor requiring a wider range of capacities, the Superduty has added horsepower and a superior cutting quality. Model 3350 is equipped with a ¾ HP motor ...to supply the torque required to cut a wide range of material thickness (16 gauge through 30 gauge) at operating speeds of up to 100 FPM. The aluminum – magnesium twist eliminators permit a knife arrangement for cutting strips as narrow as 1½" in width.*

***Model 3353:*** This is the Superduty Slitter with a 3- phase, 1 HP motor with the same cut capacities and speed as the Model 3350.

### **Standard features include:**

- ⊕ 3" diameter cold-roll turned, ground and polished shafts mounted in dual wall ball bearings
- ⊕ Bearing are lubricated for life series
- ⊕ Gauge mounting on each side permits left or right hand operation
- ⊕ End frames are aluminum-magnesium alloy
- ⊕ The exclusive GARY Torsion Tube Assembly makes it a lightweight rugged unit
- ⊕ Heavy gauge steel table with "T" bar reinforcement
- ⊕ Slitter knives are proven GARY "Quickset" design manufactured from toolsteel
- ⊕ Knives are "reversible", intervals between sharpening is double that of a single edge knives
- ⊕ 2 sets of standard 3" x 5" x ¾" wide high-carbon tooling is included
- ⊕ 60 FPM standard operating speed
- ⊕ Heavy duty roller chain drive powered by ¾ HP gearmotor with thermal overload
- ⊕ Transformer steps down control voltage to 110 for operator safety
- ⊕ Stripper fingers provide for a twist free cut
- ⊕ Standard 110/220 V -1 Ph. on **Model 3350**; 220/440 V – 3 Ph on **Model 3353**

***The affordable  
GARY SLITTER ....  
Don't settle for anything less!***

*Contact your machinery dealer and ask him for a demonstration. If you don't have a dealer or supplier in your area feel free to contact us direct. We'll be glad to answer any questions you may have.*

JWK Machinery Sales Co., Inc  
2837 Lower Breckenridge Loop NW  
Salem, OR 97304  
Tel 503-581-1516  
Fax 775-618-5508  
sales@machinetoolsjwk.com

*MODEL 3351*  
**THRIFTY 48" SLITTER**

Width overall	58"
Width between frames	50 <sup>15</sup> / <sub>16</sub> "
Maximum sheet width	49 <sup>15</sup> / <sub>16</sub> "
Standard table height	36"
Depth overall	36"
Arbor diameter	3"
Knife dimensions	5" O.D. x 3/4"
Motor HP	1/2 HP
Feed speed (FPM)	40 FPM
Voltage	110V – 1 Ph.
Weight	480 Lbs.

*MODEL 3350/3353*  
**SUPERDUTY 48" SLITTER**

Width overall	62"
Width between frames	50 <sup>7</sup> / <sub>16</sub> "
Maximum sheet width	49 <sup>15</sup> / <sub>16</sub> "
Standard table height	36"
Depth overall	36"
Arbor diameter	3"
Knife dimensions	5" O.D. x 3/4"
Motor HP	3/4 HP
Feed speed (FPM)	60 FPM
Voltage	110V / 220V – 1 Ph.
Weight	600 Lbs.

### Slitter Capacity – Number of cuts

Thickness			MODEL		
			3351 Thrifty	3350 Super Duty	3353 (3 Phase) Super Duty
Ga.	In.	Mm.			
30	.015"	.30	6	12	12
28	.018"	.37	4	8	8
26	.021"	.45	3	6	6
24	.027"	.60	3	4	4
22	.033"	.75	2	4	4
20	.039"	.91	2	3	3
18	.051"	1.2	1	2	2
16	.063"	1.5	1	1	1
14	.078"	1.8			
12	.108"	2.6			
10	.137"	3.4			

**We now offer Stripper Rings for the Superduty Slitters. This is beneficial for light gauge prepainted material. (This will reduce the cut capacity. Please consult factory on your exact requirements)**

\* Cutting capacity is limited by allowable number of knives on the machine.

